

**Drying cabinet TSS... / TS... for
drying and storage of e.g.
SMD components, pcb's, assembled feeders,
and any items that generally need to be stored in a dry place.**

Dehumidification by zeolite



Gässlesweg 6
D-75334 Straubenhardt
Tel.: +49 (0) 7082 49180
Fax: +49 (0) 7082 60436
www.imo-ag.com info@imo-ag.com

TSS2011-19 DC



TS2011-19 DC



Specifications: (changes reserved)

Drying until min. 0.5% rH
Display 0 ... 99% rH
Regeneration at 5% rH
Regeneration time approx. 1.5 hour
Power supply: 230V 50-60Hz
Power consumption: max. 550 W
Energy consumption: 1 kWh / 24 h

Dimensions: 145 x (93 + 17) x 74 cm H x W x D
5 drawer 84 x 70 x 19,5 / 34,5 cm W x D x H
Capacity depending drawer 45 Kg
Colour: RAL 7035, powder-coated,
electrically dissipative
Weight: 153 Kg

Dimensions: 198 x (92 + 17) x 61 cm H x W x D
Color: light gray similar RAL7035
4 shelves per cabinet, each (50 kg capacity)
Weight: 102 Kg

USB port for configurations software, diagnostic information and functions, firmware update.

Send bug reports by email for support.

LAN for Web, display the current moisture in the cabinet, the operating mode and status, diagnostic information and functions, MPFS update.